



WELL BALANCED CYLINDERS WITH AN INFINITE LIFE!



Brushed alloy finish provides better grip on wet cylinders.



Balanced to help diver maintain a horizontal position.



Oxygen cleaned and ready for immediate use.



Unlimited cylinder life reduces cost.



Globally certified to ensure legal use in many countries.



Industry standard 3/4" 14 NPSM thread type.

WWW.SCUBAIR.COM.AU

WELL BALANCED CYLINDER WITH INFINITE LIFE

These well balanced cylinders provide a comfortable, horizontal dive experience. The brushed, alloy finish provides superior grip.

The unlimited life design reduces ownership cost. The cylinder also has global certification. This ensures that it is legal in Australia, New Zealand, North America, Europe and many other countries around the world.

It's perfect for divers and charter boats that travel across borders.



SPECIFICATIONS

Product Code	Air Capacity at Service Pressure CF	Service	Test	Water	Diameter	Length	Weight	Unlimited Design Life	Certification
		Pressure Bar	Pressure Bar	Capacity Litres	mm	mm	kg		
S19xv	19	207	310	2.7	111	450	3.4	✓	ISO 7866
S63xv	63	207	310	9.0	184	550	12.0	✓	ISO 7866
S80xv	80	207	310	11.1	184	660	14.3	✓	ISO 7866
S80xx	80	228	342	10.3	184	645	15.2	✓	ISO 7866
S85xx	85	228	342	10.8	184	667	15.7	✓	ISO 7866
S95xx	95	228	342	11.3	184	700	16.5	✓	ISO 7866

Thread type : 3/4" 14 NPSM

SCUBAIR SCUBA VALVE

Our valves are manufactured with high precision to ensure longevity and reliability. We have standardised production with a combo valve suitable for use with cylinder service pressures ranging from 207 to 230 Bar. Our valves are fitted with a 310 Bar (4500 PSI) burst disc to ensure we comply with the ASNZ standard which stipulates that burst discs must go off before the cylinder reaches test pressure.

FEATURES

- Combination Scuba Valve with a removable plug to convert from the standard Yoke Connection to a Din 230 outlet
- Burst Disc that complies with New Zealand and Australian regulations
- Flow Restrictor to minimise hazard
- Oxygen cleaned



SPECIFICATIONS

Part Number	Description	Inlet Thread	Height on Cylinder (mm)	Weight (grams)
SVCOMBO	Combination Scuba Valve with a removable plug to convert from the standard Yoke Connection to a Din 230 Connection. Suitable for service pressures 207 to 230 Bar and fitted with a 4500 PSI Burst Disc.	3/4" 14 NPSM	76mm	648